

TECHNICAL DATA SHEET

Bonndeco Interior Plus

Modified Acrylic Resin Emulsion plus Negative ion

Product Description


Bonndeco Interior Plus is high-efficiency anti-mold topcoat is combined of modified acrylic emulsion and weather-resistant pigment. It's unique and core technology to prevent the growth of mold and algae on the wall paint surface. It is environmental product with low V.O.C. and low formaldehyde. The product is excellent in hiding power, adhesion, scrub resistance and suitable for residential, hotels, house, hospitals for interior walls and ceiling.

Features & Benefits

- Excellent opacity
- Good fungus resistance
- Cost effective, Economic but good quality
- Good moisture resistance
- Easy Application
- Low odour
- Washable

Typical Painting System

Preparation	System	
Surface should be smooth, clean and dust free.	Sealer	Bonndeco Ultra Sealer (1 coat)
	Topcoat	Bonndeco Interior Plus (2 coats)



Bonndeco Interior Paint

Application Surfaces

It is suitable for the application to interior surfaces of the following substrates:-

Precast Concrete
Poured in Place Concrete
Plaster (Mortar), Stucco, GRC
Tile Filler, Existing paint film

Application Locations

It is suitable for the application to interior surface of the following locations:-

Walls and columns
Ceilings and beams
Fence walls, Roof parapets,
Bends, etc.

Application

Roller, Spray, Brush

Glossiness

Matt

Color

Standard color chart from Bonndeco
tailor made color

Package available

23 kg/can

Thinning ratio

5 ~ 10%

Drying time

At least two (2) to eight (8) hours,
depending on the weather condition at
the time of application.

Theoretical spreading ratio

Approximately 80 - 90 m² / 2 coats / can

Remarks:-

1. The recommended coverage rates, including those of normal wastage, are for reference only. Actual coverage may vary depending on the working condition of the site, the degree of evenness and smoothness of the substrate surface, and the pattern of the texture sample as selected and approved by the architect or client.
2. We reserve the right to change or adjust the composition of material used in the specification of our products due to our constant research and development to improve of the quality of our products.

TECHNICAL DATA SHEET

Bonndeco Interior Plus

Modified Acrylic Resin Emulsion plus Negative ion

Properties		Result
USEPA Method 24	VOC Content	<10g/L
Preliminary Examination of Paint BS EN ISO 1513:2010	Condition in container (i) Surface skin (ii) Consistency (iii) Separation into layers (iv) Sediment (v) Visible impurities	No No gelling No No No
Through dry time BS EN ISO 9117-1:2009	Through dry time, hr. Average wet film thickness of test specimen, μm Average dry film thickness of test specimen, μm	$\frac{1}{2}$ 50-55 22
Fineness of grind BS EN ISO 1524:2013	Measurement 1, to the nearest 5 μm Measurement 2, to the nearest 5 μm Measurement 3, to the nearest 5 μm Mean, to the nearest 5 μm	40 40 40 40
Contrast ratio (hiding power) BS EN ISO 2814:2006	Chart 1 Chart 2 Chart 3 Mean contrast ratio, % Average wet film thickness of test specimen, μm Average dry film thickness of test specimen, μm	91.5 92.0 92.2 92 105-110 35
Specular gloss (85°)	Reading 1 Reading 2 Reading 3 Mean reading Average wet film thickness of test specimen, μm	5.9 5.7 5.9 6 75-80
1. Lead, Cadmium, Barium and Mercury content – USEPA Method 3051A/ USEPA Method 6010 2. Chromium VI content – USEPA Method 7196A 3. Ref. CPSC-CH-C1001-09.3	Lead content Cadmium content Barium content Mercury content Chromium VI content Phthalates content Benzyl butyl phthalate (BBP) Dibutyl phthalate (DBP) Di-(2-ethylhexyl) phthalate (DEHP) Diisononyl phthalate (DINP) Diisodecyl phthalate (DIDP) Di-n-octyl phthalate (DNOP)	<0.001 % by wt. <0.001 % by wt. <0.001 % by wt. <0.001 % by wt. <0.001 % by wt. <0.001 % by wt. <0.001 % by wt. <0.001 % by wt. <0.001 % by wt. <0.001 % by wt. <0.001 % by wt.

Remarks:-

- The recommended coverage rates, including those of normal wastage, are for reference only. Actual coverage may vary depending on the working condition of the site, the degree of evenness and smoothness of the substrate surface, and the pattern of the texture sample as selected and approved by the architect or client.
- We reserve the right to change or adjust the composition of material used in the specification of our products due to our constant research and development to improve the quality of our products.

TECHNICAL DATA SHEET

Bonndeco Interior Plus

Modified Acrylic Resin Emulsion plus Negative ion

Surface Treatment & Condition Requirement

New Surface

- Substrates must be properly cured before applications.
- Application surface must be smooth and free of voids or sharp projections.
- Any application surface such as precast concrete, with excess pinholes, honeycomb, cracks, uneven or porous condition, should be filled up prior to the application.
- Any application surface, with laitance, efflorescence, dust, rust, oil grease, curing agent etc. must be removed completely by brushing, sanding or other effective means.
- Recheck surface after repair to assure satisfactory condition prior to Bonndeco application.

Old Surface

- All loose coating on the application surface should be removed by wire brushing, Sanding or other effective means.
- Any laitance, efflorescence, dust, rust or oil grease must be removed completely by brushing, sanding or other effective means.
- All defective areas, hollow plasters and spoiling concrete must be hacked off.
- Defective wall surfaces must be repaired by filling cracks or re-plastering of hacked off portions.
- To paint areas must be cleansed by high pressure water jet at 1,500 psi and all surfaces should be of the sound, clean, dry and sufficiently smooth that accepted as an appropriate substrate for the application of Bonndeco Products.

Fungus

Remove by high-pressure water jet wash and treated with anti-fungus solutions. Allowed to dry before painting.

Grease

Clean Off with mild detergent and a little solvent. Wash thoroughly to remove all trace.

Application Procedure

- Shake and stir thoroughly to get a complete dispersion of pigment.
- Use standard practice, either by rolling, brush or spraying, to ensure conformance to the specification requirement.
- Drying time may take at least two (2) to eight (8) hours at 10°C - 20°C
- Workers, applying in confined areas, are required to wear protection masks and exhaust ventilation should be properly supplied to the confined area.

Precautions in use

Handling and storage

- Do not use near flames
- All workplaces to always have specific ventilating equipment in operation.
- Particular precautions to be taken for good ventilation during application and while drying, and precautions taken to avoid any inhaling of fumes.
- During handling, precautions to be taken to avoid any skin contact and as necessary, gas mask against organic gas or fresh air supplying masks to be worn and also use head towels, wear protective eyeglasses, long sleeved protective gowns, neck protecting towels, protective gloves, etc.
- When coat is spilled, wipe with waste cloths to be kept stored in water filled containers.
- Until final disposal, all waste cloths that have been exposed to coat, hardeners or thinners, and leftover coat, spray dust, etc. for disposal shall be kept doused in water filled containers.
- After handling or application, hands to be thoroughly washed and extensive gargling is advised.
- The handles on the upper part of the tin containers are solely for carrying the tins. Please do not use ropes and hooks on the handles for hanging the tins.
- During storage, containers are to be tightly sealed and stored out of any direct sunlight or any exposure to rain, in a cool, well ventilated area.
- Please store away from any foreign instruction by third parties and out of the reach of children.

Cleaning Up

- Clean all equipment with clean water immediately after use

Remarks:-

- The recommended coverage rates, including those of normal wastage, are for reference only. Actual coverage may vary depending on the working condition of the site, the degree of evenness and smoothness of the substrate surface, and the pattern of the texture sample as selected and approved by the architect or client.
- We reserve the right to change or adjust the composition of material used in the specification of our products due to our constant research and development to improve of the quality of our products.