

# ポリマーセメント系基礎巾木用塗材

Coating material for polymer cement baseboard

kikusui

## 基礎ガード

### BASIC GUARD

"Basic Guard" is a colored polymer cement-based slightly elastic coating material. It has excellent crack followability and carbonation prevention function, and maintains foundation baseboards for a long time.



Before

基礎ガードを  
塗装すると



Painting the  
Base guard

After

#### 新築にも

"Strong foundations are necessary for earthquake preparedness. To prevent deterioration, we recommend painting."

#### 改修にも

"We will clean up small cracks, fractures, and discolored areas. Fashion starts from the feet."

#### 特長

- ①コンクリートひび割れに追従
- ②省工程
- ③中性化抑止効果
- ④水系塗材で環境にやさしい

This type of flexible coating film can follow small cracks.  
這種微彈性的塗料膜可以跟隨微小的裂縫。

Since this product does not require a topcoat (with color types), it can be completed with one material, reducing costs and saving time.  
由於這種產品是無需上塗層的（有著色類型），因此可以用一種材料完成，降低成本並縮短時間

The high adhesion of the polymer cement coating can prevent the infiltration of neutralizing substances.  
通過聚合物水泥塗層的高附著力，可以防止中和物質的侵入

This is a water-based surface treatment paint, so it has less odor and can be used with peace of mind.  
這是一種水性表面處理塗料，因此氣味較少，可以安心使用

#### 施工工程



Base Material



Undercoat



Main Material



Complete

## 標準色



■KG-01



■KG-02



■KG-03



■KG-04



■KG-05



■KG-06

\*The colors are for reference only.

\*Please check the actual color on the sample board. Please note that the color and gloss shown above may differ from the actual product due to the printing process.

Process	Materials/Formulation	Application Tools	No. of Coating	Number of times Interval time (23°C)	Consumption (kg/m <sup>2</sup> )
Preparation (if necessary)	Dig up the ground around the foundation baseboards to expose the entire rising surface of the foundation, completely remove any soil that has adhered to it, and leave it as a dry, clean surface.				
Surface Preparation	Remove dirt, unhardened cement powder, sand, oil, and other deposits with a wire brush, swab, sandpaper, and rag, leaving the surface dry and clean.				
Undercoat	Basic Guard Power:16kg Mixed Liquid:12kg Fresh Water: 0.8-1.2L	Wool roller, brush, etc.	1	1 or more	56-93m <sup>2</sup> /28kg 0.3-0.5kg/m <sup>2</sup>
Main Material Coating	Basic Guard Power:16kg Mixed Liquid:12kg Fresh Water: 0.8-1.2L	Porous roller	1	---	28-40m <sup>2</sup> /28kg 0.7-1.0kg/m <sup>2</sup>

1. The above values are all standard values. However, there may be some variation in each value depending on the construction method and conditions.
2. If powder remains on the inner wall or bottom of the mixing container, it may cause lumps. Therefore, please remove the powder attached to the inner wall with a spatula or other tool and mix it again with a mixer.
3. If lumps occur, please remove them with a sieve or similar tool before using.
4. The recommended working time is 60 minutes (at 20°C). Please make sure to use it up before that time.
5. Please prepare a separate mixing container and measure the appropriate amount to be used, then mix it accordingly.
6. Please make sure that cleaning water from construction tools and equipment does not flow into rivers or penetrate into the soil.
7. If acid used for cleaning porcelain tiles comes into contact with the surface, it may cause discoloration or even dissolve the tiles. If there is a possibility of acid used for cleaning porcelain tiles coming into contact with painted surfaces, it is essential to perform masking on the painted surfaces.
8. Please refer to the SDS for details on general precautions regarding the handling of the product.
9. There may be some color difference depending on the construction method used.
10. If rain or condensation is expected, please avoid applying the coating as it may cause problems such as blistering, peeling, or whitening of the film immediately after application.
11. If the coating is applied below or above the specified amount, it may cause various defects. Please apply the required amount of coating as specified.
12. Depending on the situation, it may be necessary to apply a primer before coating.

### 用途

Foundation skirting board painting

### 色調

6 Colours

### 艶

MATT

### 荷姿

28kg/set  
Power 16kg/bag  
Mixed Liquid 12kg/can



**BONNTILE HONG KONG LTD**  
邦盛建材香港有限公司

Flat C2, 11/F, Hang Fung Industrial Building, Phase 2, 2G Hok Yuen Street, Hung Hom, Kowloon, Hong Kong  
Tel: 2341 9201 Fax: 2763 5348 www.bonntile.com.hk



### 注意点

掲載製品を取り扱う際は、各製品のSDS及び標準施工仕様書、注意事項を守って施工してください。  
※上記の各種製品データは、**kikusuiダウンロードサイト**でご確認ください。



**菊水化学工業株式会社** 本社 ☎ 052-300-2222(代)

ホームページ <https://www.kikusui-chem.co.jp/>



仙台 ☎ 022-706-5710

大阪 ☎ 06-7668-5320

東京 ☎ 03-3981-2500

福岡 ☎ 092-935-4610

名古屋 ☎ 0568-69-5200



- このパンフレットは2022年8月の情報により作製しております。
- このパンフレットに掲載の製品は、予告なしに仕様や取り扱いを変更することがあります。
- 諸官公庁等の特記仕様がある場合は、それを優先して下さい。

vol.13 22.8.Bi50 ㊗