

Kikusui

Thick Finish Coating Material

厚塗層材料

Stucco Series



A high-quality finish coating that blends in harmoniously with nature
一個與自然和諧融合的高品質塗層



Kikusui Stucco Series

Thick Finish Coating Material
厚塗層材料

Kikusui Stucco Series

Kikusui tile Lock/R NSK-0412018 F★★★★

Kikusui Elastic Lock NSK-0306312 F★★★★

The Kikusui Stucco Series is a thick finish coating material primarily composed of synthetic resin emulsion. It provides a natural and three-dimensional finish with a wide range of colors, enhancing the appearance of walls. Moreover, the durable coating film offers long-term protection to the building's aesthetics.

Kikusui Stucco 系列是一種主要合作樹脂乳液組成的厚塗層材料。它通過自然而立體的表面處理和豐富多樣的色調，為牆面營造出獨特的效果。同時，這種耐久性優秀的塗膜能夠長期保護建築物的美觀外觀。

The wide range of color variations is delightful
多樣豐富的色彩選擇令人愉悅

You can choose any color tone you like
您可以選擇任意的色調

A wide range of colors can be obtained, from light to dark shades. As the main material can be colored, you can choose any color tone you like.

可以獲得從淺色到深色的廣泛色彩範圍。由於主材料可以着色，因此您可以選擇任何喜歡的顏色調。



To stay beautiful forever
希望永遠保持美麗

Strong coating performance
強韌的塗膜性能

It forms a coating film that is resistant to efflorescence and less prone to cracking. Additionally, applying a topcoat further enhances its durability.

它形成了一種不易產生白華和裂紋的塗膜。此外，塗層塗料可以進一步提高基耐久性。



Exterior thick coating material E

Kikusui Tile Lock/R

It is commonly referred to as acrylic stucco. It is a coating material that excels in workability, using synthetic resin emulsion as the binding agent. It not only offers high coating performance but also encompasses various functions such as color and design for decorative applications.

通常被稱為丙烯酸灰泥。它是一種作業性優良的塗料材料，使用合成樹脂乳液作為黏結劑。它不僅具有高度的塗膜性能，還具備色調和設計等裝飾面的多種功能。

Impressive and solid finishing is delightful
厚重的完成令人愉悅

Impressive and solid finishing pattern
厚重的裝飾圖案

You can create a solid and impressive wall surface by using textures that give a three-dimensional effect.

通過使用具有立體感的紋理，您可以打造出厚重而令人印象深刻的牆面。



Because it is a material with excellent workability

因為它是一種具有優良可操作性的材料。

Safe and economical
安全經濟

As it is a water-based material, it is environmentally friendly and has excellent workability. In other words, it helps reduce construction costs, making it cost-effective.

由於是水基材料，因此對環境友好且具有出色的操作。換句話說，它有助於降低施工成本，是物有所值的。



Exterior thick coating material E

Kikusui Elastic Lock

It is commonly referred to as elastic stucco. It features a robust rubber-like coating film that traditional elastic stucco lacks. Additionally, it has minimal surface tack and is a thick finishing coating material with excellent resistant to contamination and waterproofing properties.

通常被稱為彈性灰泥。它具有傳統彈性灰泥所沒有的堅韌橡膠狀塗膜。此外，它具有較少的表面黏性，並且是一種具有優異的耐污染性和防水性能的厚塗飾塗料。

Choose from a variety of natural textures and finishes. In addition to the design unique to thickly coated materials, it is highly durable and waterproof. 可以從多種自然紋理和飾面中進行選擇，除了厚塗材料獨特的設計外，它還具有高耐久性和防水性能。

Finish Pattern Variations
完成圖案變化

Various surface finishes available. You can choose according to your preference.
提供各種表面處理. 您可以根據自己的喜好選擇.

Kikusui Tairok R

Spray gloss finish
噴塗亮光飾面



カラーNo. KN030D

Convex treatment glossy finish
凸面處理亮光飾面



カラーNo. KN020B

Spray gloss finish
噴塗亮光飾面



カラーNo. KN060A

Convex treatment glossy finish
凸面處理亮光飾面



カラーNo. KN048A

Kikusui Elastic Lock

Spray finish
噴塗飾面



カラーNo. KN022F

Convex treatment finish
凸面處理飾面



カラーNo. KM120B

(Note) 1. Due to printing, colors and gloss may vary slightly. Please confirm the actual color and gloss with sample boards.
由於印刷原因, 顏色和光澤可能略有不同. 請與樣板確認實際顏色和光澤度.

2. Dark or primary colors may fade more easily compared to other colors.
與其他顏色相比, 深色或原色可能更容易褪色.

Applicable base 適用基地

• Substrate that can be directly applied Mortar, exposed concrete surfaces, etc.
可直接施工的基材砂漿, 裸露混凝土表面等.

*For lightweight aerated concrete (ALC), use Kikusui Foundation, etc., and for rough surfaces, use BR#15, etc. to prepare the base.
對於輕質加氣混凝土 (ALC), 使用菊水地基等, 對於粗糙表面, 使用BR#15等來準備基底.

Standard Application Specification 標準應用規範

Finishing 飾面	Process 流程		Materials 材料	Application tools 應用工具	No. of coats 施工 層數	Interval time (23°C) 間隔時間	Theoretical usage (kg/m ²) 理論用量
Common to all types 適用於 所有類型	Surface Preparation 表面處理		To prepare the surface, remove dirt, unhardened cement powder, sand, oil, and any other adhering matter using a brush, peeling spade, sandpaper, cloth, or any other suitable means. It is essential to ensure that the surface is completely dry before proceeding. 準備表面, 請使用刷子, 剝離鏟, 砂紙, 布或其他適當工具清除污垢, 未硬化的水泥粉末, 沙子, 油和其他附着物. 在進行下一步之前, 務必確保表面完全乾燥.				
	Main material coating 主要材質塗層 (specified with aggregate)	Base coating 基層塗	Kikusui Tairok R aggregate included Main material 主材: 25kg Fresh water 清水: 1.0~2.0L	Stucco Gun Diameter 噴槍口徑:8mm Blow pressure 吹壓: 0.5~0.6MPa	1	3 hours or more 3 小時或以上	10~16m ² /25kg 1.5~2.5kg/m ²
		Pattern coating 圖案塗層	Kikusui Tairok R aggregate included Main material 主材: 25kg Fresh water 清水: 0~0.5L	Stucco Gun Diameter 噴槍口徑:8~12mm Blow pressure 吹壓: 0.2~0.3MPa	1	24 hours or more 24 小時或以上 Convex treatment 0.5 or less	7.1~10m ² /25kg 2.5~3.5kg/m ²
Kikusui Tairok R	Main material coating 主要材質塗層 (aggregate removal specification)	Base coating 基層塗	Kikusui Tairok R aggregate included Main Material: 20kg Aggregate 主材: 25kg Fresh water 清水: 1.8~3.6L	Stucco Gun Diameter 噴槍口徑:8mm Blow pressure 吹壓: 0.5~0.6MPa	1	3 hours or more 3 小時或以上	18~30m ² /45kg 1.5~2.5kg/m ²
		Pattern coating 圖案塗層	Kikusui Tairok R aggregate included Main Material 主材: 20kg Fresh water 清水: 0~0.9L	Stucco Gun Diameter 噴槍口徑:8~12mm Blow pressure 吹壓: 0.2~0.3MPa	1	24 hours or more 24 小時或以上 Convex treatment within 0.5	13~18m ² /45kg 2.5~3.5kg/m ²
	Convex treatment (*1) 凸面處理		Apply paint thinner to a plastic roller and press it down evenly 將油漆稀釋劑塗在塑膠滾筒上並均勻地壓下去.				
	Top coat (*2) 面漆	Water- based Acrylic finish 水性丙烯酸 面漆	View top acrylic Main material 主材: 16kg Fresh water 清水: 0.8~1.6L	Airless spray etc. 無氣噴塗, 等	2	3 hours or more 3 小時或以上	45~64m ² /16kg 0.25~0.36kg/m ²
		Water- based Urethane finish 水性聚氨酯 面漆	View top urethane Main material 主材: 16kg Fresh water 清水: 0.8~1.6L	Airless spray etc 無氣噴塗, 等.	2	3 hours or more 3 小時或以上	45~64m ² /16kg 0.25~0.36kg/m ²
	Undercoat 底漆		Kikusui Primer Super E Main material 主材: 15kg Premixed 預混合	Brush, wool roller, airless spray, etc. 刷塗, 羊毛滾塗, 無氣噴塗, 等	1	3 hours or more 3 小時或以上	80~150m ² /15kg 0.10~0.19kg/m ²
	Kikusui elastic lock	Main material coating 主要材質塗層	Base coating 基層塗	Kikusui elastic lock Main material 主材: 20kg Fresh water 清水: 0.5~1L	Stucco Gun Diameter 噴槍口徑:8mm Blow pressure 吹壓: 0.5~0.6MPa	1	6 hours or more 6 小時或以上
Pattern coating 圖案塗層			Kikusui elastic lock Main material 主材: 20kg Fresh water 清水: 0~0.2L	Stucco Gun Diameter 噴槍口徑:8mm Blow pressure 吹壓: 0.2~0.3MPa	1	Convex treatment within 0.5 凸面處理0.5以內	6~13m ² /20kg 1.5~3.3kg/m ²
Convex treatment (*1) 凸面處理		Apply paint thinner to a plastic roller and press it down evenly 將油漆稀釋劑塗在塑膠滾筒上並均勻地壓下去.					



Bonntile Hong Kong Ltd

邦盛建材有限公司

www.Bonntile.com.hk

Flat C2, 11/F, Hang Fung Industrial Building, Phase 2, 2G Hok Yuen Street, Hung Hom, Kowloon, Hong Kong

Tel: 2341 9201

Fax: 2763 5348